

What we claim as our invention is:

CLAIMS:

- [c1] 1. An apparatus for applying data representing a watermark to data representing an image, the apparatus comprising: a source of location and time data;
- an error coding unit connected to receive the location and time data for applying a forward error correction algorithm to the said location and time data and outputting error coded data therefrom;
- a code spreading unit coupled to receive the error coded data for spreading the error coded data to create spread data by repeatedly outputting portions of the error coded data a number of times therefrom;
- a DES code generator for generating and outputting data representing a DES code;
- a combiner for combining the spread data and the DES code and outputting watermark data representing a location and time specific watermark;
- a receiver for receiving signals containing said data representing an image as DCT coefficients in transform space, which data is received in an encoded and compressed form on a signal medium, and for receiving an apparatus specific key;
- a decoding circuit responsive to the apparatus specific key for decoding and decompressing the received signals to recover the data representing an image therefrom;
- a control circuit for analyzing at least a component of the image data to determine an attribute thereof and to output a signal representative of the attribute;
- a marking control unit, coupled to receive the signal from the control circuit, the image data from the source and the watermark data from the combiner, for adding the watermark data to the image data depending on a characteristic of the attribute and a characteristic of the image data;
- an inverse DCT transform circuit connected to receive the watermarked image data and to convert the same from data representing the image as DCT coefficients in transformation space to data representing the image in pixel space;

09881017 "051301
T01T9D "T03860

a pixel processor connected to receive the data representing the image in pixel space for converting the pixel data into a format suitable for display; and

a projector connected to receive formatted pixel data from the pixel processor for projecting the image represented thereby.

[c2] 2. An apparatus as claimed in claim 1, further comprising a source of program key data and a source of frame index data uniquely identifying each frame in a moving image, and wherein the DES code generator is connected to the source to receive the frame index data therefrom and to generate a DES code depending on the frame index data and the program key data.

[c3] 3. An apparatus as claimed in claim 1, further comprising a source of program key data and a source of frame index data uniquely identifying a predetermined number of frames in a moving image, and wherein the DES code generator is connected to the source to receive the frame index data therefrom and to generate a DES code depending on the frame index data and the program key data.

[c4] 4. An apparatus as claimed in claim 2, wherein the combiner comprises an exclusive-OR (XOR) gate for combining the spread data and the DES code on a bit-by-bit basis according to an XOR function.

[c5] 5. An apparatus as claimed in claim 4, wherein the control circuit is connected to receive data representing the luminance component of the image, and is configured to determine as said attribute an amplitude value of the luminance component as the \log_2 of the value of the luminance component.

[c6] 6. An apparatus as claimed in claim 5, wherein the marking control unit is arranged to generate as a generated value from the watermark data a positive or negative value and to add the generated value to the image data depending on the \log_2 of the value of the luminance component being greater than a predetermined threshold.

[c7] 7. An apparatus for applying data representing a watermark to data representing an image, the apparatus comprising:

means for supplying location and time data;

means for receiving the location and time data, for applying error coding to the said location and time data, and outputting error coded data therefrom;

spreading means coupled to receive the error coded data for applying a spreading function to the error coded data and outputting spread data therefrom;

means for generating and outputting data representing a pseudo-random code;

means for combining the spread data and the pseudo-random code and outputting watermark data representing a location and time specific watermark;

means for supplying image data representing an image in transformation space;

means for analyzing at least a component of the image data to determine an attribute thereof and for outputting a signal representative of the attribute; and

marking means, coupled to receive the signal representative of the attribute, the image data and the watermark data, for adding the watermark data to the image data depending on a characteristic of the attribute and a characteristic of the image data.

[c8] 8. An apparatus as claimed in claim 7, wherein the means for generating and outputting data representing a pseudo-random code is configured to apply a forward error correction algorithm to the location and time data.

[c9] 9. An apparatus as claimed in claim 7, wherein the spreading means is configured to apply the spreading function depending on a spreading factor.

[c10] 10. An apparatus as claimed in claim 7, wherein the spreading means is configured to apply a spreading function in which bits in the error coded data are repeated a number of times.

09881017 "061301
T081990

[c11] 11. An apparatus as claimed in claim 7, wherein the means for generating and outputting data representing a pseudo-random code comprises a DES engine.

[c12] 12. An apparatus as claimed in claim 11, further comprising means for supplying program key data and wherein the DES engine is connected to the means for supplying to receive the program key data therefrom and to generate a pseudo-random code depending on the program key data.

[c13] 13. An apparatus as claimed in claim 11, further comprising means for supplying frame index data uniquely identifying each frame in a moving image, and wherein the DES engine is connected to the means for supplying frame index data to receive the frame index data therefrom and to generate a pseudo-random code depending on the frame index data.

[c14] 14. An apparatus as claimed in claim 11, further comprising means for supplying frame index data uniquely identifying a predetermined number of frames in a moving image, and wherein the DES engine is connected to the means for supplying frame index data to receive the frame index data therefrom and to generate a pseudo-random code depending on the frame index data.

[c15] 15. An apparatus as claimed in claim 12, further comprising means for supplying frame index data uniquely identifying each frame in a moving image, and wherein the DES engine is connected to the means for supplying frame index data to receive the frame index data therefrom and to generate a pseudo-random code depending on the frame index data and the program key data.

[c16] 16. An apparatus as claimed in claim 7, wherein the combining means comprises an exclusive-OR (XOR) gate for combining the spread data and the pseudo-random code on a bit-by-bit basis according to an XOR function.

09881017-061301
"061301" 09881017

[c17] 17. An apparatus as claimed in claim 7, wherein the means for analyzing at least a component of the image data is connected to receive data representing the luminance component of the image.

[c18] 18. An apparatus as claimed in claim 7, wherein the means for analyzing at least a component of the image data is connected to receive data representing a chrominance component of the image.

[c19] 19. An apparatus as claimed in claim 7, wherein the means for analyzing at least a component of the image data is configured to determine an amplitude value as the attribute.

0531017
2703360
"T0E1304"
[c20] 20. An apparatus as claimed in claim 19, wherein the amplitude is determined as the \log_2 of a value of the component of the image data.

[c21] 21. An apparatus as claimed in claim 7, wherein the marking means is arranged to generate as a generated value from the watermark data a positive or negative value and to add the generated value to the image data depending on the said characteristic of the attribute.

[c22] 22. An apparatus as claimed in claim 21, wherein the means for analyzing at least a component of the image data is configured to determine an amplitude value as the attribute and the characteristic is the amplitude value being greater than a predetermined threshold.

[c23] 23. An apparatus as claimed in claim 22, wherein the amplitude is determined as the \log_2 of a value of the component of the image data.

- [c24] 24. An apparatus as claimed in claim 7, further comprising:
means for receiving signals containing said data representing an image in an encoded and compressed form on a signal medium, and for receiving an apparatus specific key;
decoding means responsive to the apparatus specific key for decoding and decompressing the received signals to recover the data representing an image therefrom.
- [c25] 25. An apparatus as claimed in claim 24, wherein the signals are conveyed on the medium as data packets and the means for receiving signals comprises data interface means for receiving the data packets.
- [c26] 26. An apparatus as claimed in claim 24, wherein the means for receiving signals is arranged to receive the apparatus specific key through a medium different than the medium from which the encoded and compressed data signals are received.
- [c27] 27. An apparatus as claimed in claim 24, wherein the signals are encoded using DES encryption and the decoding circuit comprises a DES decryption engine.
- [c28] 28. An apparatus as claimed in claim 24, wherein the signals are compressed using a lossless compression technique.
- [c29] 29. An apparatus as claimed in claim 28, wherein the lossless compression technique comprises run-length encoding.
- [c30] 30. An apparatus as claimed in claim 24, wherein the signals are compressed using a lossy compression technique.
- [c31] 31. An apparatus as claimed in claim 30, wherein the lossy compression technique comprises block quantization.

[c32] 32. An apparatus as claimed in claim 24, further comprising inverse transforming means circuit coupled to receive the watermarked image data and to convert the same from data representing the image in transformation space to data representing the image in pixel space.

[c33] 33. An apparatus as claimed in claim 32, further comprising pixel processing means coupled to receive the data representing the image in pixel space for converting the pixel data into a format suitable for display by a projector.

[c34] 34. An apparatus as claimed in claim 33, further comprising an interface means for buffering data from the inverse transforming means for the pixel processing means.

[c35] 35. An apparatus as claimed in claim 33, further comprising displaying means coupled to receive formatted pixel data from the pixel processor for displaying the image represented by the pixel data.

[c36] 36. A method of applying data representing a watermark to data representing an image, the method comprising:

supplying location and time data;

applying a forward error correction algorithm to the said location and time data to produce error coded data;

applying a spreading function to the error coded data to create spread data by repeating portions of the error coded data a number of times;

generating data representing a DES code;

combining the spread data and the DES code to create watermark data representing a location and time specific watermark;

receiving signals containing said data representing an image as DCT coefficients in transform space, which data is received in an encoded and compressed form on a signal medium;

09881017-061401

receiving an apparatus specific key;

decoding and decompressing the received signals responsive to the apparatus specific key to recover the data representing an image therefrom;

analyzing at least a component of the image data to determine an attribute thereof and to create a signal representative of the attribute;

adding the watermark data to the image data depending on a characteristic of the attribute and a characteristic of the image data;

converting the watermarked image data from data representing the image as DCT coefficients in transformation space to data representing the image in pixel space;

converting the pixel data into a format suitable for display; and

projecting the image represented by the formatted pixel data.

093801/06101
10330/06101

[c37]

37. A method as claimed in claim 36, further comprising:

supplying program key data;

supplying frame index data uniquely identifying each frame in a moving image;

and

generating the DES code depending on the frame index data and the program key data.

[c38]

38. A method as claimed in claim 36, further comprising:

supplying program key data;

supplying frame index data uniquely identifying a predetermined number of frames in a moving image; and

generating the DES code depending on the frame index data and the program key data.

[c39]

39. A method as claimed in claim 37, further comprising combining the spread data and the DES code on a bit-by-bit basis according to an XOR function.

[c40] 40. A method as claimed in claim 39, further comprising:
receiving data representing the luminance component of the image; and
determining as said attribute an amplitude value of the luminance component as
the \log_2 of the value of the luminance component.

[c41] 41. A method as claimed in claim 40, further comprising:
generating as a generated value from the watermark data a positive or negative
value; and
adding the generated value to the image data depending on the \log_2 of the value of
the luminance component being greater than a predetermined threshold.

[c42] 42. A method of applying data representing a watermark to data representing
an image, the method comprising:
supplying location and time data;
applying error coding to the said location and time data to produce error coded
data;
applying a spreading function to the error coded data to produce spread data;
generating data representing a pseudo-random code;
combining the spread data and the pseudo-random code to produce watermark
data representing a location and time specific watermark;
supplying image data representing an image in transformation space;
analyzing at least a component of the image data to determine an attribute thereof
to produce a signal representative of the attribute; and
adding the watermark data to the image data depending on a characteristic of the
attribute and a characteristic of the image data.

[c43] 43. A method as claimed in claim 42, further comprising applying a forward
error correction algorithm to the location and time data.

09/03/01 10:17:06:1301

[c44] 44. A method as claimed in claim 42, further comprising applying the spreading function depending on a spreading factor.

[c45] 45. A method as claimed in claim 42, further comprising applying a spreading function in which bits in the error coded data are repeated a number of times.

[c46] 46. A method as claimed in claim 45, wherein the pseudo-random code generator is generated by way of a DES engine.

[c47] 47. A method as claimed in claim 46, further comprising receiving program key data and generating a pseudo-random code depending on the program key data.

[c48] 48. A method as claimed in claim 46, further comprising:
supplying frame index data uniquely identifying each frame in a moving image;
and
generating a pseudo-random code depending on the frame index data.

[c49] 49. A method as claimed in claim 46, further comprising:
supplying frame index data uniquely identifying a predetermined number of frames in a moving image; and
generating a pseudo-random code depending on the frame index data.

[c50] 50. A method as claimed in claim 47, further comprising:
supplying frame index data uniquely identifying each frame in a moving image,
and
generating a pseudo-random code depending on the frame index data and the program key data.

0988017.061301
FOI b7c b7d

53. A method as claimed in claim 42, further comprising supplying data representing the luminance component of the image.

54. A method as claimed in claim 42, further comprising determining an amplitude value as the attribute of the image.

[c56] 56. A method as claimed in claim 42, further comprising:
generating as a generated value from the watermark data a positive or negative value; and
adding the generated value to the image data depending on the said characteristic of the attribute.

111
 112
 113
 114
 115
 116
 117
 118
 119
 120
 121
 122
 123
 124
 125
 126
 127
 128
 129
 130
 131
 132
 133
 134
 135
 136
 137
 138
 139
 140
 141
 142
 143
 144
 145
 146
 147
 148
 149
 150
 151
 152
 153
 154
 155
 156
 157
 158
 159
 160
 161
 162
 163
 164
 165
 166
 167
 168
 169
 170
 171
 172
 173
 174
 175
 176
 177
 178
 179
 180
 181
 182
 183
 184
 185
 186
 187
 188
 189
 190
 191
 192
 193
 194
 195
 196
 197
 198
 199
 200
 201
 202
 203
 204
 205
 206
 207
 208
 209
 210
 211
 212
 213
 214
 215
 216
 217
 218
 219
 220
 221
 222
 223
 224
 225
 226
 227
 228
 229
 230
 231
 232
 233
 234
 235
 236
 237
 238
 239
 240
 241
 242
 243
 244
 245
 246
 247
 248
 249
 250
 251
 252
 253
 254
 255
 256
 257
 258
 259
 260
 261
 262
 263
 264
 265
 266
 267
 268
 269
 270
 271
 272
 273
 274
 275
 276
 277
 278
 279
 280
 281
 282
 283
 284
 285
 286
 287
 288
 289
 290
 291
 292
 293
 294
 295
 296
 297
 298
 299
 300
 301
 302
 303
 304
 305
 306
 307
 308
 309
 310
 311
 312
 313
 314
 315
 316
 317
 318
 319
 320
 321
 322
 323
 324
 325
 326
 327
 328
 329
 330
 331
 332
 333
 334
 335
 336
 337
 338
 339
 340
 341
 342
 343
 344
 345
 346
 347
 348
 349
 350
 351
 352
 353
 354
 355
 356
 357
 358
 359
 360
 361
 362
 363
 364
 365
 366
 367
 368
 369
 370
 371
 372
 373
 374
 375
 376
 377
 378
 379
 380
 381
 382
 383
 384
 385
 386
 387
 388
 389
 390
 391
 392
 393
 394
 395
 396
 397
 398
 399
 400
 401
 402
 403
 404
 405
 406
 407
 408
 409
 410
 411
 412
 413
 414
 415
 416
 417
 418
 419
 420
 421
 422
 423
 424
 425
 426
 427
 428
 429
 430
 431
 432
 433
 434
 435
 436
 437
 438
 439
 440
 441
 442
 443
 444
 445
 446
 447
 448
 449
 450
 451
 452
 453
 454
 455
 456
 457
 458
 459
 460
 461
 462
 463
 464
 465
 466
 467
 468
 469
 470
 471
 472
 473
 474
 475
 476
 477
 478
 479
 480
 481
 482
 483
 484
 485
 486
 487
 488
 489
 490
 491
 492
 493
 494
 495
 496
 497
 498
 499
 500
 501
 502
 503
 504
 505
 506
 507
 508
 509
 510
 511
 512
 513
 514
 515
 516
 517
 518
 519
 520
 521
 522
 523
 524
 525
 526
 527
 528
 529
 530
 531
 532
 533
 534
 535
 536
 537
 538
 539
 540
 541
 542
 543
 544
 545
 546
 547
 548
 549
 550
 551
 552
 553
 554
 555
 556
 557
 558
 559
 560
 561
 562
 563
 564
 565
 566
 567
 568
 569
 570
 571
 572
 573
 574
 575
 576
 577
 578
 579
 580
 581
 582
 583
 584
 585
 586
 587
 588
 589
 590
 591
 592
 593
 594
 595
 596
 597
 598
 599
 600
 601
 602
 603
 604
 605
 606
 607
 608
 609
 610
 611
 612
 613
 614
 615
 616
 617
 618
 619
 620
 621
 622

[c58] 58. A method as claimed in claim 57, wherein the amplitude is determined as the \log_2 of a value of the component of the image data.

[c59] 59. A method as claimed in claim 42, further comprising:
receiving signals containing said data representing an image in an encoded and compressed form on a signal medium;
receiving an apparatus specific key; and
responding to the apparatus specific key by decoding and decompressing the received signals to recover the data representing an image therefrom.

[c60] 60. A method as claimed in claim 59, wherein the signals are conveyed on the medium as data packets.

[c61] 61. A method as claimed in claim 59, wherein the apparatus specific key is received via a medium different than the medium from which the encoded and compressed data signals are received.

[c62] 62. A method as claimed in claim 59, wherein the signals are encoded using DES encryption.

[c63] 63. A method as claimed in claim 59, wherein the signals are compressed using a lossless compression technique.

[c64] 64. A method as claimed in claim 63, wherein the lossless compression technique comprises run-length encoding.

[c65] 65. A method as claimed in claim 59, wherein the signals are compressed using a lossy compression technique.

03081017 061401

[c66] 66. A method as claimed in claim 65, wherein the lossy compression technique comprises block quantization.

[c67] 67. A method as claimed in claim 59, further comprising converting the watermarked image data from data representing the image in transformation space to data representing the image in pixel space.

[c68] 68. A method as claimed in claim 67, further comprising converting the pixel data into a format suitable for display by a projector.

[c69] 69. A method as claimed in claim 68, further comprising displaying the image represented by the pixel data.

[c70] 70. An apparatus for adding a watermark to a moving image as it is displayed, the apparatus comprising:

a watermark generator in which data representing a watermark is generated containing first information pertaining to the displaying of the moving image and protected by forward error encoding and second information pertaining to the displaying of the moving image and protected by scrambling; and

a watermark applicator for applying the watermark data to image data representing substantially all of the moving image depending on a characteristic of the data.

[c71] 71. An apparatus as claimed in claim 70, wherein the watermark generator is connected to receive at least one of location data and time data as said first information pertaining to the displaying of the image.

[c72] 72. An apparatus as claimed in claim 70, wherein the watermark generator is connected to receive at least one of program data identifying the moving image and frame

03/03/01 09:13:01

data unique in identifying each frame of the moving image as said second information pertaining to the displaying of the image.

[c73] 73. An apparatus as claimed in claim 70, wherein the watermark generator is connected to receive at least one of program data identifying the moving image and frame data unique in identifying a predetermined number of frames of the moving image as said second information pertaining to the displaying of the image.

[c74] 74. An apparatus as claimed in claim 72, wherein the watermark generator is connected to receive at least one of location data and time data as said first information pertaining to the displaying of the image.

[c75] 75. An apparatus as claimed in claim 70, wherein the watermark generator comprises an error correcting circuit for receiving said first information pertaining to the displaying of the image and applying said forward error encoding.

[c76] 76. An apparatus as claimed in claim 70, wherein the watermark generator comprises a DES engine for receiving said second information pertaining to the displaying of the image and scrambling the same by generating a pseudo-random code depending on the second information.

[c77] 77. An apparatus as claimed in claim 70, wherein the watermark applicator comprises an amplitude control module for controlling application of the watermark data to the image data depending on the amplitude of the image data.

[c78] 78. An apparatus as claimed in claim 70, wherein the watermark applicator comprises an adder for adding the watermark data to the image data.

[c79] 79. A watermarking system for applying data representing a moving image to produce watermarked image data which is output to a display device for display of the

09884017-06301
FILED "06301"

moving image represented thereby, in which system information identifying at least one of the system, the image and the displaying of the image is convolutionally encoded and spread and information identifying at least one of the system, the image and the displaying of the image is encrypted so as to produce the watermark data which is applied to substantially all data representing the moving image with the exception of data having a value below a determined level in order to minimize the introduction of visible noise and other artifacts into the image by the watermark.

09931047-061301
T0E790-7078860